

OVERVIEW

Flexicoat HC is a flexible acrylic based exterior coating with excellent resistance in extreme climatic conditions. The coating has good flexibility and an attractive semi-gloss finish which is resistant to dirt pick-up from the atmosphere. The system also allows water vapour to pass from the structure to the atmosphere but will not allow water ingress. Flexicoat HC has excellent resistance to mould and algae growth.

PROPERTIES

Flexicoat HC is formulated using acrylic binders and additives which give it elastic properties, long life, fade resistance and an attractive semi-gloss finish. It is available in a range of 20 attractive shades.

AREAS OF USE

Flexicoat HC is primarily designed for exterior facades such as high-rise buildings, office blocks, hotel construction and hospitals. It gives an attractive semi-gloss finish to all types of exterior facades.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are brushed and scraped away. Surface defects should be repaired with Terramix or Acrylic Filler. Apply 2 coats of TERRACO Penetrating Primer to ensure the surface is sound and well bound. Old surfaces should be treated with a soda / water solution, rinsed and allowed to dry before application.

APPLICATION & CLEANING OF TOOLS

Flexicoat HC can be applied by spray or roller to achieve the required texture. Apply 2 coats diluting the first coat with 20% of water. The second coat should not be diluted.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Flexicoat HC coating is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Waterproof acrylic coating.
Binder	Acrylic.
Pigments	Lime and light fast.
Thinning	With water.
Primer	2 coats of <i>TERRACO</i> Penetrating Primer
Drying Time	3 - 4 hours.
Toxicity	Non-toxic.
Consumption	1 - 1.5 m ² /ltr
Colour	Available in 20 standard shades.
Packaging	25kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com